

Warmup - Primer



Overview

A ready to use, bond enhancing and solvent-free single component primer for the preparation of absorbent and non-absorbent floors and walls with or without surface heating.

Ideal for use before laying Warmup Peel and Stick systems, levelling compounds and tile adhesives.

Suitable for use as a deep penetrating primer on absorbent surfaces.

Suitable Substrates

Concrete	Metal	Epoxy Paints
Cement Screeds	Tile Backer Boards	Epoxy Moisture Barriers
Anhydrite Screeds	Terazzo floors	Water-Resistant Adhesive Residues
Magnesite Screeds	Natural Stone	MSP's
Levelling Compounds	Ceramic Tiles	Abraded Mastic asphalt
Timber	Vinyl	

- » Not suitable for use on PUR pre-coatings or melamine faced boards.
- » Contacting substrates, adhesives and compounds must be free of migrating elements.

Recommended for use

We recommend the use of this primer with the following Warmup systems:

Electric	Hydronic
DCM-PRO	Nexxa 12
StickyMat	Total-16
StickyMat 3D	
StickyMat 12V	

Technical specifications

Product Code	ACC-Primer
Typical Consumption	Porous Substrate: 20m ² /l (Diluted 1:1 with Water) Non-Porous: 14m ² /l (Undiluted)
Application Temperature	15°C - 25°C
Ideal Application Air Humidity	40% - 60%
Drying Time	30 - 60 minutes (at 20°C and 65% relative humidity) » Higher humidity and/or lower temperatures delay drying » Lower humidity and/or higher temperatures accelerate drying
Density	1100 kg/m ³
Colour	Purple
Shelf Life	12 Months in original container when kept out of direct sunlight and at temperatures between 10°C and 25°C, avoiding frost. Diluted product must be used on the day of dilution or discarded.
Certification	EC1-PLUS GISCODE D1 TRG5 610 - Solvent-free
Product Contains	2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. Can cause allergic reactions. EU limit value for the product (Cat. A / h Wb): 30 g / l (2010). This product contains maximum 30 g / l VOC. In the event of a reaction, remove yourself or the affected person from the application area, seek medical advice and wash thoroughly with soap and water.

Contact

Warmup plc
www.warmup.co.uk
uk@warmup.com
T: 0345 345 2288
F: 0345 345 2299

Warmup GmbH
www.warmupdeutschland.de
de@warmup.com
T: 04431 - 948 70 0
F: 04431 - 948 70 18

Warmup plc ■ 704 Tudor Estate ■ Abbey Road ■ London ■ NW10 7UW ■ UK
Warmup GmbH ■ Ottostraße 3 ■ 27793 Wildeshausen ■ DE

Warmup - TS - Primer - V1.2 2021-08-20_EN